

# PRODUCT INFO



## SADDLE-BAG

Saddle-Bag with roll closure in 3 sizes



Snap lock for attaching the bag to the saddle

Velcro for additional fastening of the bag to seat post, prevents moving of the bag

Roll closure with buckle and D-rings

Highly reflective 3M Scotchlite reflector

Loop for mounting tail light (optional)



Including mounting set



Fastening straps for spring saddles, usable as an alternative possibility to fix the bag to the saddle; available as accessory



„Top Product“ by magazine RAD-touren (for version 2012), 1/2012



„Winner of Test“ with result „Outstanding“ in category „large Saddle-Bags“ MountainBIKE 10/2011

Size	height cm/in.	width cm/in.	depth cm/in.	vol. L/cu.in	weight g/oz.
S	9/3.5	12/4.7	7/11 2.8/4.3	0.8/49	210/7.4
M	9/3.5	14/5.5	7/12 2.8/4.7	1.3/7.9	250/8.8
L	10/3.9	23/9.1	7/16 2.8/6.3	2.7/165	330/11.6

## SPECIFICATIONS:

- + Waterproof Saddle-Bag for mountain, road or touring bikes
- + Size S, perfect for roadbikes (e.g. for spare tube)
- + Size M, perfect for MTBs (pocket tool, tube)
- + Size L provides enough space for a jacket and the necessary small items (alternative to the backpack)
- + Snap lock for quick fitting and removal
- + Reliable waterproof roll closure with D-rings for additional bracing and locking
- + Highly effective Scotchlite reflector ensures safety in the dark
- + On bikes without mudguards the bag shields the rider from splash to a certain extent, ideally size L
- + Snap lock is adjustable and can easily get attached to different saddles
- + Saddle Bag meets all requirements of the VELOTECH test, review board for bicycle technic
- + Fixing system is also available as an accessory (e.g. for a second bike, art. code E97)
- + Velcro tape suitable for seat posts up to 34,9 mm (e.g. foldable bike Birdy)
- + Fastening straps for spring-mounted saddles, where the snap lock cannot be used (optional accessory art. code F96E)

**Contents:** Saddlebag with mounting set

**Note:** Maximum load 3 kg/7 lbs!

**Note:** In order to meet standard IP64 (6=dustproof, 4=protected against splash water coming from all directions) the roll closure must be rolled at least 3-4 times.